



**BRICKING
SOLUTIONS**
A DIVISION OF **BROKK**

HEAVY DUTY SHOCK ABSORBED SAFETY INSPECTION CAGE 2 MAN AND 4 MAN



Safe, Portable and Easy set up

1144 VILLAGE WAY | MONROE, WASHINGTON 98272 | USA
800.621.7856 | 360.794.1277 | FAX 360.805.2521
INFO@BRICKINGSOLUTIONS.COM | WWW.BRICKINGSOLUTIONS.COM

SAFETY INSPECTION CAGE

FEATURES & BENEFITS



1.5M (5 feet) of **portable protection** designed & certified by a professional engineer. Rated for 114kg (**250lbs**) dropped from 455mm (18 in) with a **3:1 safety factor**. A shock absorbed panel increases safety.

Fabricated from **6061 T6 aluminum** with a steel mesh cover secured with wing nuts. Protruding bolts on top of frame hold the wire mesh in place.



Easily carried by 2 people using flip-up handles attached to a safety gate. **Shoulder harness** is standard for increased stability.

All sides are **color coded** for easy assembly. Adjustable height with **4 independently adjustable legs** for the varying surfaces and thickness of a coated kiln.



On request, unassembled pieces can fit in most openings. Assembled in 15 minutes and **stores on a pallet**.

	Min Coating ID	Max Coating ID	Width	Approx Weight
2 MAN CAGE	2.7M	3.5M	1.5M (5ft)	100 - 114 kg (220 - 250 lbs)
4 MAN CAGE	3.6M	4.3M	1.5M (5ft)	295 kg (650 lbs)
Clearance cage to coating: min .30M (12 in), max 455mm (18 in)			Minimum clearance head to cage: .28M (18 inches)	
Vehicle required to install cages where coating ID is above 4.3M				

Cage Panel Dims any combo	61 cm (24 in)	76 cm (30 in)	91 cm (36 in)	99 cm (39 in)	107 cm (42 in)
---------------------------	---------------	---------------	---------------	---------------	----------------

OUR SAFETY / INSPECTION CAGES ARE DESIGNED TO PROTECT YOUR WORKERS FROM FALLING COATING / BRICK UP TO 114 kg (250 lbs) FROM 455mm (18 in) WITH A 3:1 SAFETY FACTOR. OUR CAGES ARE NOT DESIGNED NOR WILL THEY PROTECT YOU FROM MOLTEN COATING, HEAT, OR TOXIC FUMES, ETC.